

# TSUNAMI BILGE PUMPS

With their innovative engineering and compact design, Tsunami pumps deliver high output from a small package. We use the most advanced material available, including the best quality bearings and state-of-the-art brushes, alloys and magnets. Our patented shaft seal prevents leaks caused by misalignment and our caulked and tinned wiring eliminates wicking, prevents water damage and resists corrosion.



## NMMA Numbers

Part No.	NMMA No.	IMCI (CE) Certificate No.
4606 Series	2456898	PATT042
4608 Series	2456899	PATT043
4609 Series	2456900	PATT044
4612 Series	2456901	PATT046
4613 Series	2456902	PATT045

## Specifications

Model No.	Rated Voltage	Amp Draw	GPH Output @ Design Voltage 13.6 VDC					GPH Output @ Nominal Voltage 12.0 VDC					Fuse Size	Hose Size
			0 ft.	3.3 ft.	6.7 ft.	Max Head	Amp Draw	0 ft.	3.3 ft.	6.7 ft.	Max Head			
T500	12	1.8	600	440	260	9 ft.	1.4	550	360	160	8 ft.	3-amp	3/4" I.D.	
T800	12	3	800	660	540	13 ft.	2.5	760	600	400	11 ft.	4-amp	3/4" I.D.	
	24	1.3	800	660	540	13 ft.	1.1	760	600	400	11 ft.	2-amp	3/4" I.D.	
T1200	12	3.5	1200	900	700	11 ft.	3	1100	810	480	9 ft.	5-amp	1-1/8" I.D.	
	24	1.5	1200	900	700	11 ft.	1.3	1100	810	480	9 ft.	2-amp	1-1/8" I.D.	

## Pump Dimensions

Model No.	A	B	C	D	E
T500	2-3/4"	2-7/8"	3-5/8"	3/4" I.D.	3-1/8"
T800	3-1/8"	3-1/4"	4-3/8"	3/4" I.D.	3-1/2"
T1200	3-1/8"	3-1/4"	4-3/8"	1-1/8" I.D.	3-3/4"

