

POWERFUL PERFORMANCE, IN JUST THE RIGHT SIZE.



New! SI-TEX SVS-460C and SVS-560CF

The new SVS-460C and SVS-560CF prove that you don't need a big boat — or a big bankroll — to benefit from SI-TEX's rugged construction and professional-grade performance. These compact chartplotter and chartplotter/sounder systems deliver the goods for any vessel, from center console skiffs to sailboats to light commercial boats. The SVS-460 chartplotter features a 4.3" high-resolution color LCD and compact case. The SVS-560 features a 5" high-resolution color LCD with a built-in dual-frequency fishfinder.

SI-TEX
MARINE ELECTRONICS

Real. Reliable. Ready for Action.

www.si-tex.com | 631-996-2690

find us on **facebook**

Both are packed with features, including:

- 52-channel GPS w/standard internal antenna (optional external antenna)
- "Dual fuel" charting with C-MAP and Navionics cartography
- Units pre-loaded w/Navionics Gold North American Chart Card
- Global GPS compatibility (U.S., European Galileo, Russian Glonass and Asian QZSS)
- Brilliant LED backlighting for daylight readability
- Easy, intuitive operation and control
- SVS-460 retails for just \$449/\$499 w/ext. antenna
- SVS-560 retails for just \$649/\$699 w/ext. antenna

These new-for-2015 products give boaters exactly what they expect from SI-TEX: Rugged construction, versatile, no-nonsense performance and features that really matter. Not to mention outstanding value for your hard-earned money. Check out these powerful, affordable and reliable new charting and charting/fishfinding systems at your local SI-TEX dealer!

GENERAL SPECIFICATIONS

1. Display Screen
SVS-460: 4.3 inch Color LCD with LED backlight
SVS-560: 5 inch Color LDC with LED backlight
2. Resolution
Smart4: WQVGA (480 x 272 pixels)
Smart5: WVGA (800 x 480 pixels)
3. Power Supply
DC 12V-36V(±10%)
Smart4: 4W(without fishfinder)/ 6W(with fishfinder)
Smart5: 5W(without fishfinder)/ 7W(with fishfinder)
4. Operating Temperature
Display Unit -15°C~+50°C
Antenna Unit -25°C~+70°C
5. Performance Standard
IMO Resolution MSC.112(73)
6. Option
MicroSD, *External GPS Antenna, **Transducer

CHARTPLOTTER SPECIFICATIONS

1. Display Method Mercator Projection
2. Display Mode
True motion / N/S/E/W up / Course up / Head up
3. Latitude Limits Between 85° N to 85° S
4. Map Scale 0.05nm to 1500nm
5. Map Datum WGS-84
6. Waypoints **20,000 points**
*Total of 16 colors and 16 icons are selectable each point with name tag (6 alphanumeric characters)
7. Track Points **50,000 points(2 types)**
8. Route Max capacity 100 Routes
*20 WPTs per each Route. Each with name tags (8 alphanumeric characters)
9. Draw Point 1,000 points
10. Area Name 1,000 points
11. Chart Data Standard w/Navionics Gold
C-MAP MAX optional
12. Output Data NMEA-0183
13. Input Data NMEA-0183
14. Alarm Arrival, Anchor, XTE, Interval timer, Userline

GPS RECEIVER SPECIFICATIONS

1. GNSS Receiver Capabilities
GPS L1 C/A cpde
GLONASS L1OF/
QZSS L1 C/A code
Galileo E1B/E1C/L1
2. Number of Channel
52 channels
3. Horizontal Positioning Accuracy
Autonomous 2.5m (CEP 50%)
4. Sensitivity
Acquisition -148 dBm
Tracking -165 dBm
Reacquisition -162 dBm
5. Nav Update
1Hz, 5Hz)
6. Support
DGPS, SBAS(EGNOS,WAAS, MASA, GAGAN)

FISHFINDER SPECIFICATIONS (560 only)

1. Display Mode
Normal (single/dual-frequency), Bottom-lock.
Bottom-zoom, A-scope
2. Frequency
50 and 200 KHz (single or dual)
3. Output Power
600W
4. Range speed
600W - 2.5m - 600m
5. Image speed
Fixed 8 speeds (4/1, 2/1, 1/1, 1/2, 1/4, 1/8, 1/16, 1/32) and stop
6. Rejection
Interference rejection:3 levels, Noise rejection:4 levels
7. Function
Gain(auto/manual), Range(auto/manual), Shift(auto/manual), White/Black line
Support speed sensor, Water temperature



SI-TEX SVS-460C



SI-TEX SVS-560CF

SI-TEX
MARINE ELECTRONICS