

THE ORIGINAL
FATSAC
 BALLAST BAG CO.

Barefoot International & Fat Sac Mfg.
 3879 North Richards Street
 Milwaukee, WI 53212

PHONE 414-964-3668 ■ FAX 414-964-5767 ■ E-MAIL orders@fatsac.com ■ WEB www.fatsac.com



PART#	DESCRIPTIONS * Fittings Used with W709-SUPA Pump* •Fittings made for automatic ballast systems•
W720	EPOXY CEMENT FOR FITTINGS, 25ML OR 1 OZ TUBES (AKA:50805) — MIX WELL BEFORE USE!
W730 *	SUPA PUMP QUICK CONNECT W/CHAIN & CAP — USED FOR FILLING FATSACS
W739 *	SUPA PUMP QUICK CONNECT CAP ONLY
W731	FAT SAC PLUGS — SAC VALVE THREADS MALE
W732	FEMALE GHT (GARDEN HOSE THREAD) — MALE QUICK CONNECT - FILL FATSACS WITH GARDEN HOSE
W733-SS •	1" BARBED END — SAC VALVE THREADS MALE — SHOULD USE PERMANENT EPOXY CEMENT (W720)
W734 *	SUPA PUMP QUICK CONNECT — FOR WATER INTAKE ON BOTTOM OF SUPA PUMP
W772	HEYCO NYLON 6/6 AUTO AIR BLEEDER VALVE
W736-SS •	3/4" QUICK CONNECT — SAC VALVE THREADS — SHOULD USE PERMANENT EPOXY CEMENT (W720)
W737 •	3/4" BARBED END — SAC VALVE THREADS — SHOULD USE PERMANENT EPOXY CEMENT (W720)
W738 *	SUPA PUMP QUICK CONNECT — 1-1/8" BARBED FITTING - GOES ON END OF SUPA PUMP HOSE
W740 •	FLOW-RITE 3/4" STRAIGHT QUICK CONNECT SOCKET
W741 •	FLOW-RITE 1-1/8" STRAIGHT QUICK CONNECT SOCKET
W742 •	FLOW-RITE 3/4" ELBOW QUICK CONNECT SOCKET
W746 •	FLOW-RITE 1-1/8" ELBOW QUICK CONNECT SOCKET
W743-DOUBLE	DOUBLE SIDED 1-1/8" QUICK CONNECT FITTING
W743-SS •	1-1/8" QUICK CONNECT - SUCTION STOP SAC THREADS — USE PERMANENT EPOXY CEMENT (W720)
W744 *	1 WAY CHECK VALVE FOR SUPA PUMP
W774	INFLATION VALVE WITH 3/4" NPT MALE SAC THREADS (FOR FILLING FATSACS WITH AIR)
W748 •	1-1/8" QUICK CONNECT TO 1" BARBED
W749	AIR RELEASE PLUG — TURN TO RELEASE AIR. FOR MANUAL AIR VENTING.
W753 •	1" BARBED IN-LINE CHECK VALVE
W755 •	1-1/8" BARBED IN-LINE CHECK VALVE
W729 *	FEMALE PUMP QUICK CONNECT - MALE SAC VALVE THREADS - THE BOTTOM OF THE W730 FITTING
W743-REGAL	1-1/8" QC FITTING WITH 1/2" NPT THREADS (USED W/ S2002 JOHNSON PUMP 13.5 GPM) FOR HOSE
S1004 •	FLOW-RITE 90 DEGREE ELBOW THRU HULL FITTING (BARBED END)
S1003 •	FLOW-RITE STRAIGHT THRU HULL FITTING (BARBED END)
S1007	1-1/2" FLOW-RITE QUICK CONNECT ELBOW FITTING (FITS W775 QC)
S1008	1-1/2" FLOW-RITE QUICK CONNECT STRAIGHT FITTING (FITS W775 QC)
S1006	1-1/2" X 12 UNF QC HF TALLULA PUMP FITTING (FITS S2001 30GPM PUMP) FOR ATTACHING HOSE
S1005	FAT SAC SOCKET SPLITTER + USB PORTS + ON/OFF SWITCHES (RUN 2 PUMPS W/ 1 CIG. ADAPTER)
W746-PLUG •	FLOW-RITE 1-1/8" PLUG FITS INSIDE W746/W741 FITTINGS TO CAP OFF PNP SYSTEMS IN BOATS

IMPORTANT: Use Permanent Epoxy Cement W720 on the threads of the W733-SS, W736-SS, W737, W743-SS, and W747 when screwing them into Fat Sacs.