

## VLB5

2.8mm fixed lens, white housing

## Features

- Supports up to 2MP @ 30fps
- Full HD resolution over coax
- Supports HD-TVI, CVI, AHD, and 960H Analog
- IR Range: 65' (depending on scene reflection)
- 12VDC Operation (power supply not included)

1/2.9" CMOS, 2MP

- IP67 compliant, weather resistant
- Junction box included
- 5 year warranty

Image Sensor

## **Camera Specifications**





## **Operating & Unit Specifications**

Power	12VDC (power supply not included)
Power Consumption	IR OFF: < 1W; IR ON: < 3W
Operating Temperature	-22°F~ 122°F
Operating Humidity	10% ~ 95% RH
Unit Dimensions	6.59" (L) x 2.93" (W) x 2.93" (H)
Unit Weight	.82 lbs.

0	'	*
Minimum Illumination	0 lux (IR ON)	
Image Size	1920 x 1080	
Video Output	AHD/TVI/CVI/CVBS	
Image System	PAL/NTSC	
Electronic Shutter	Auto: 1/50s ~ 1/100000s (PAL); 1/60s ~ 1/100000s (NTSC)	
IR Distance	32.8ft ~ 65.6ft	
Frame Rate	30fps (60Hz); 25fps (50Hz)	
Lens Mount	M12	
S/N Ratio	≥ 52dB (AGC OFF)	
Functions		
Function Control		OSD (COC Control)
Day & Night		Yes, Smart IR
Digital WDR		Yes
DNR		3D DNR
AGC		Yes
Auto White Balance		Yes
Compensation		
compensation		BLC
Front Light Compensati	on	BLC Yes
	on	

**Optional Accessories** 

Mirror

Image Setting

Defect Correction

Angle Adjustment



Pan (0° ~ 360°); Tilt (0° ~ 80°); Rotation (0° ~ 360°)

<sup>1</sup>Camera is defaulted to HD-TVI. ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/16/21

Yes

Yes

Auto

