

## **IND-19**

## **LED- Sunlight Readable Industrial/Marine LCD Monitor**

This product features the latest in LCD technology with 1,500nit LED backlights rated at 100,000 hours life.

This product features optically bonded anti -reflective glass, perfect 1000:1 dimming, DVI, VGA, HDMI and Mil Spec. OSD controls.

## **Features**

- --19.0" TFT LCD
- --1,280 X 1,024 Resolution(SXGA)
- --10 to 38VDC Power Input, AC/DC Brick Power Supply Included
- --Applications: In-Outdoor, Marine, Air craft, Vehicles.

## **Specifications**

LCD Type	TFT Active Matrix LCD (16.7 Million colors)
Display Size	19.0"
Resolution	1,280 x 1,024(SXGA)
Contrast Ratio	1,000:1
Brightness	LED Backlight Type- 1,500 nit(min.)
Panel Surface	Anti-Glare Coating with Tempered Glass
Inputs	DVI, VGA, HDMI(With PIP/POP)
Mounting Options	VESA / Flush/U-Bracket mounted
View Angle	170(H) 170 (V)
Response Time	3m/sec
Light Source	Light Emitting Diodes
Input Voltage	10 to 38VDC Power Input, AC/DC brick power supply included
Power Consumption	34W
Out-dimensions	14.96"(W)x17.51"(H)x2.23"(D), 380(W)x445(H)x56.8(D)mm
Operating Range	-10C ~ 60C
Cases Color	Black ,Dark Gray
IP Rating	Front Side:IP65, Rear Side:IP32
Warranty	2 yrs
Dimming Range	1000:1 (dimming control to dark to full bright)
Weight	13.67 LBS(6.2Kg)

