

# Softlink 4.0 - Soft shackle - Dia 4 mm - Length: 80 mm

Part #21224



## Description

SoftLink is a soft shackle developed by Wichard for recreational sailors looking for performance and ease of use. For the same strength, SoftLink is 4 or 5 times lighter than a 316L stainless steel shackle.

No knowledge of ropework required Replaces shackles and snap hooks Easy to fit and easy to open Remarkably light and strong

Re-usable

3 sizes available

Materials: stainless steel and Dyneema SK 78

Loop diameter: 4 mm Loop length: 80 mm

#### **Applications**

Fastenings

Replaces shackles and snap hooks

#### Technical information

	Materials	316L stainless steel grade Dyneema SK78
<u> </u>	Loop diameter (mm)	4
	Loop length (mm)	80
	Working load (kg)	2300
	Breaking load (kg)	3000
	Weight (g)	23

## Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.

The safety factor is 5 times the breaking load.  $\label{eq:WLL} WLL = Breaking \, load \, / \, 5$ 

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures