

# Watertight U-bolt - Dia IO mm - Length: 90 mm - Black

Part #65351





## Description

Fully dropforged product with high quality stainless steel Outstanding working and breaking loads

Complete watertightness thanks to the resistant rubber collar (black colour)

Easy installation (no need to use a waterproof sealant) For any kind of fastening applications (shrouds, lifeline, blocks...)

Delivered with bolts and counterplate Max tightening torque: 36 Nm

#### **Applications**

Various fastening applications: shrouds, lifelines, blocks...

### Technical information

lack

Materials	316L stainless steel grade
Colour	Black
Length (mm)	90
Working load (kg)	3600
Breaking load (kg)	7000
Weight (g)	219
A (mm)	40
B (mm)	26
C (mm)	45
D diameter (mm)	10

## Caption



Working load (WL): for nautical applications



Working Load Limit (WLL): for industrial applications only.

The safety factor is 5 times the breaking load.  $WLL = Breaking\ load\ /\ 5$ 

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.