


# HR key pin shackle with bar - Dia 6 mm

Part #91433





## Description

Forged D shackle in HR stainless steel grade (17,4 PH) Outstanding working and breaking load

A HR shackle can be up to 60% more resistant than a shackle in 316L stainless stee

WLL: only for industrial applications (lifting i.e...)

CE marking and batch number

### **Applications**

Applications requesting high loads

Perfect product for halyards or applications requiring to open /close the shackle often

Do not use for moorring applications

#### Technical information

Materials

lack

	<b>5</b>
Working load (kg)	600
Breaking load (kg)	2200
Weight (g)	53
A (mm)	45
B (mm)	16
C (mm)	6
D (mm)	13
E (mm)	4
F (mm)	60
G (mm)	37
L (mm)	15

HR 17.4 PH stainless steel grade

## Caption



Working load (WL): for nautical applications



Working Load Limit (WLL): for industrial applications only.

The safety factor is 5 times the breaking load. WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.