
Stainless Steel Straight Thru-Hulls, Threaded

- Unique multi-thread design with NPSM and NPT threads
- Offer generous thread length
- Allows for direct connection to seacocks or pipes

Caution: Stainless Steel Thru-Hull Connectors are designed for installation above the water line only.




A Flange Dia.	B Thread O.D.	C Total Length	Installation Hole Saw Size	Threads NPSM	Max Hull Thickness	OEM Part # without Gasket	Part #
1-7/8"	2-1/8"	2-1/2"	1-1/8"	3/4"	1-5/8"	66559-1	—
2-1/4"	2-1/4"	2-5/8"	1-3/8"	1"	1-3/4"	66561-1	—
3"	2-3/8"	2-3/4"	2"	1-1/2"	1-7/8"	66563-1	—

Stainless Steel 90° Thru-Hulls, Barbed

Allows installation in especially tight spaces.

Caution: Stainless Steel Thru-Hull Connectors are designed for installation above the water line only.




B

A Hose Size	B Flange Dia.	C Thread O.D.	D Thread Length	E Barb Length	F Total Length	Install. Hole Saw Size	Thread NPSM	Max Hull Thick.	OEM Part # without Gasket	Part #
3/4" I.D.	1-7/8"	1"	1-1/2"	3/4"	3-3/8"	1-1/4"	3/4"	1-1/16"	66577-1	—
1-1/8" I.D.	2-1/4"	1-3/8"	1-7/8"	3/4"	4-3/8"	1-5/8"	1"	1-1/4"	66579-1	_

Stainless Steel Scupper Valves

- The Scupper Flap is tough neoprene rubber with a molded V that fits into the grooved body to reduce backwash
- · Fasteners are concealed and corrosion-proof
- Enhanced 316 Stainless Steel Alloy

Caution: Stainless Steel Scupper Valves are designed for installation above the water line only.



A Hose Size	B Thread Dia.	C Flange O.D.	D Thread Length	E Barb Length	F Total Length	Install. Hole Saw Size	Thread NPSM	Max Hull Thick.	OEM Part # without Gasket	Part #
Threade	Threaded									
_	1-7/8"	3"	3-1/2"	_	3-7/8"	2"	1-1/2"	3"	66565-1	_
_	2-23/64"	3-5/8"	2-1/2"	_	2-7/8"	2-1/2"	2"	2"	66567-1	_
Barbed										
1-1/2"	1-7/8"	3"	3-1/2"	1-1/2"	5-1/2"	2"	1-1/2"	3"	66553-1	66553-3
2"	2-23/64"	3-5/8"	2-1/2"	1-5/16"	4-1/2"	2-1/2"	2"	2"	66555-1	_
1-1/2"	3"	1-7/8"	2-1/4"	1-1/2"	4-1/2"	2"	1-1/2"	1-3/4"	66557-1	_
Valve Accessories								BULK		
Replacement Flappers for 1-1/2"								66553Kit	_	
Replacement Flappers for 2"							66555Kit	—		







66557G





66559



66558G





F Total Length	lnstall. Hole Saw Size	Thread NPSM	Max Hull Thick.	OEM Part # without Gasket
3-3/8"	1-1/4"	3/4"	1-1/16"	66577-1
4-3/8"	1-5/8"	1"	1-1/4"	66579-1